





# GP Component




PCB Layout

Specification Type (1:2)



REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
AO			原始版本(INITIAL EDITION)	2020.12.16	m t



## CHARACTERISTICS:

1. RATED VOLTAGE: 250V AC CD
2. RATED CURRENT: 3.0AMP
3. CONTACT RESISTANCE: 30mΩ Max.
4. INSULATION RESISTANCE: 1000 MΩ MIN. 500V DC
5. Electric Pressure: Keeping 60 second in AC 500V/1mA
6. Operating temperature: -55°C~105°C
7. INSERTION/EXTRACTION FORCE PER CONTACT: 3.0Kg Max 0.3Kg Min.

01.DR0809 F X XXX XX A XXX

PIN Poles	09:9PIN	M/F Differentiates	M=Male F=Female	Hsg Color	1=Black 3=Blue 5=Yellow 2=White 4=Green 6=Purple	Plating	G00:Gold flash G01:Gold 1U" G03:Gold 3U" Gxx:Gold XXU"	B00:Bright sn B01:Bright sn 1U" B03:Bright sn 3U" Bxx:Bright sn XXU"	M00:Matte sn M01:Matte sn 1U" M03:Matte sn 3U" Mxx:Matte sn XXU"	Water Code	Specification Type	Hsg Material

	UNITS: mm [inch]		DESIGN: 牟 2020.12.16	PART NAME: DR 9P系列图
	TOLERANCE: X.X ±0.35 X.XX ±0.25 X.XXX ±0.15 Angle ±3.0°		CHECKED: 牟 2020.12.16	PART NO. 01.DR0809PXXXXXXXXXX
APPROVED: 牟 2020.12.16	SCALE:1:1 SIZE:A4		DRAW NO.	SHEET NO. 01 OF 01

东莞市跃展精密连接器有限公司  
Dongguan YueZhan Precision Connectors Co., Ltd